

0333 123 1243 www.payagroup.co.uk enquiries@payagroup.co.uk





# **iWL SERIES**

Data Sheet & Tech Spec







### Bring real mobility to payments















- Optimize revenue opportunities with 24/7 connectivity.
- Reinvent mobile payment user experience with a pocket-sized device, long battery life and fast printer.
- Bring mobility payment to your point of sale.
- Open-up a wide range of solutions for various environments (small merchants, hospitality and mobile businesses).



### **iWL SERIES**

The iWL series is designed to bring an innovative payment solution, remaining connected even in the most demanding environments.

#### **HIGHEST SECURITY**

The iWL series meets the highest security requirements and is PCI-PTS x and 3.x certifi ed with SRED & open protocol modules.

#### **ALL PAYMENT OPTIONS**

Offering EMV Chip & PIN, MagStripe and Contactless, the iWL series also enables new NFC couponing and wallet use cases.

#### **POCKET SIZED**

Designed for mobility use cases, the iWL series is a pocket-sized device. It's the world's smallest and lightest terminal.

#### **DESIGNED FOR MOBILITY**

Extended battery life, pocket-size form factor, light weight design, perfect display readability, wide backlit keypad and robust casing make the iWL series ideal for all mobility uses cases.

#### LONG BATTERY LIFE

Natively designed for mobility, Ingenico has paid specifi c attention to delivering an outstanding battery life. Depending on the use cases, the iWL series can deliver up to several days of use.

## ALL WIRELESS CONNECTIVITY

Featuring a unique portfolio of simple and multiple wireless connectivity options – GPRS, 3G, Bluetooth Class 1 & WiFi – the iWL series enhanced network quality of service, eg 3G/GPRS used as a back-up of BT. Beyond, Multicom enables a smooth integration of the iWL series in multi-devices solutions, e.g being connected in BT to an ECR, taximeter or tablet while keeping its own connection to the banking host

#### **OUTSTANDING PRINTER**

With its 30 lines per second, the iWL series printer is the fastest on the market. Reducing printing time improves on-the-spot effi ciency

#### **TELIUM 2 ADVANCED**

Powered by Ingenico, Telium 2 technology is the result of 30 years' experience in the payment industry. Secure, highly integrated and fast, Telium 2 is the world best platform to provide payment services and a library of over 2000 applications. Telium 2 is a fully scalable, reliable operating system embedded into the 20 million terminals deployed worldwide.









# **iWL SERIES**

### **FEATURES**

		iWL 220	iWL 250
Posterior	ADM 0 0 ADM 7		
Processor  Memory	ARM 9 & ARM 7 16 RAM/16 Flash 32 RAM/128 Flash Micro-SD reader	• Option Option	· :
SIM	Dual SIM	Option	Option
SAM		Up to 3	Up to 3
Card readers	Smart card Magstripe Contactless	1+2nd Option • Option	1+2nd Option • Option
Display		FSTN, Monochrome graphic, 128 x 64 pixels, White backlit 2,53"	Transmissive TFT-LCD Colour QVGA 320 x 240 pixels 4096 colours 2,81"
Keypad	Backlit operational keys Navigation keys	15 7	15 7
Thermal printer	Speed in lines/second	30 l/s	30 l/s
Terminal connectivity Wireless	WAN LAN Multicom	GPRS or 3G/GPRS Bluetooth and/or WiFl WAN & LAN	GPRS or 3G/GPRS Bluetooth and/or WiFl WAN & LAN
Terminal connectivity Wired		Micro USB type A/B (host & slave)	Micro USB type A/B (host & slave)
GPS Tracking		Option	Option
Audio	Buzzer Speaker	• Option	• Option
Power supply	Terminal/base Terminal car charger	5V 1A 5V 0,75A - option	5V 1A 5V 0,75A - option
Batteries	Li-lon	Li-lon 2200mAh	Li-Ion mAh
Terminal size	L x W x H (paper roll cage Ø 25 mm) (paper roll cage Ø 40 mm)	150mm x 78mm x 44mm 165mm x 78mm x 54mm	150mm x 78mm x 44mm 165mm x 78mm x 54mm
Weight		285g	285g
Customisation	Lens marking Printer cover flap Top casing	Option Option Option	Option Option Option
Optional base	Charge RS232 USB A USB B Modem Ethernet 10/100 Base T Bluetooth	• (2) Option Option Option Option Option Option Option Option	• (2) Option Option Option Option Option Option Option Option
Enviroment	Operating temperature Storage temperature Relative humidity, non condesning	-10°C to 45°C -20°C to 55°C 85% HR at +40°C	-10°C to 45°C -20°C to 55°C 85% HR at +40°C
Security	Online & offline	PCI PTS 2.x & 3.x	PCI PTS 2.x & 3.x



0333 123 1243 www.payagroup.co.uk enquiries@payagroup.co.uk









